VALUE series



Single-layer, non-insulated steel construction provides beauty and durability at an economical value.

STYLE AND CONSTRUCTION

- 1-layer construction (steel).
- Woodgrain embossed steel base door painted front and back for a virtually maintenance-free door.
- Quality 24 or 25 gauge steel and 2" thick frame construction for durability and longevity.
- Woodgrain textured short and long raised panel designs in 1-layer construction complement traditional home styles.

	co	LOR OPTI	ONS		PANEL OPTIONS				
					73, 94 TRADITIONAL SHORT	76 TRADITIONAL LONG			
White	Almond	Desert Tan	Sandtone	Chocolate					

MODEL SPECS									
MODELS	73	76	94						
Panel Styles	Short Traditional	Long Traditional	Short Traditional						
Steel Gauge	25	25	24						
Insulation Thickness	N/A	N/A	N/A						

	WINDCODE® AVAILABILITY CHART										
	Common oor Widths	W1**	W2	W3	W4	W5	W6	W7	W8		W9
	USE T50										
	8', 9' Wide Door	S +13 / -15 PSF	S +16 / -18.5 PSF	F S +20 / -21 PSF	FT WS +25 / -32 PSF	FTWS +30 / -32 PSF	SFT WS* +38 /-42 PSF	D W +42 /-48 PSF	D W +48 / -54 PSF	FTD +54 / -62 PSF	FT DW +62 / -72 PSF
Model 94	10', 12' Wide Door	S +12.5 / -14 PSF	S +15.5 / -17 PSF	F S +20 / -21 PSF	SFT W S* +24/-24.5 PSF	FTWS +30 / -30 or +28 / -30.5 or +32 / -32 PSF	SFT W S* +37 /-41 PSF	FTW +42 / -48 PSF			
	16' Wide Door	S +12.5 / -14 PSF	S +15.5 / -17 PSF	F S +20 / -21 PSF	● F T W S* +24 / -24.5 PSF	FT WS +30 / -30 or +28 / -30.5 or +32 / -32 PSF	SFT W S* +37 /-41 PSF	FTW +42 / -48 PSF	FT DW +46.2 /-52 PSF		
	18' Wide Door	S +12.5 / –14 PSF	SELECT W3	F S* +20 / -21 PSF	S F T W S* +25 / -25 PSF	SELECT W6	SFT WS* +37/-37 PSF	D W +42 /-46 PSF			
	S Standard Windows Available Impact Rated				W Impact Windows Available F Florida Approved			D Dade County Approved T Texas Department of Insurance Approved			

^{*} Long window availability is limited due to reinforcement requirements

^{**} For W1, Model T50 is used. Model T50 is a tongue-and-groove 1-layer door.

VALUE series



WINDCODE® AVAILABILITY CHART										
Coi	mmon Door Widths	W1**	W2	W3	W4	W 5		W6	W7	W8
		USE T50								
	8', 9' Wide Door	S +13/–15 PSF	S +16 / –18.5 PSF	F S* +20 /-21 PSF	S F T W S +25 /-32 PSF	FTWS +30 /-32 PSF		S F T W S* +38 /-42 PSF	● F T W +42 /-48 PSF	FTW +46 /-50 PSF
Model 73	10', 12' Wide Door	S +12.5/–14 PSF	S +15.5 / -17 PSF	F S +20 /-21 PSF	SFT WS* +24 /-24.5 PSF	FTWS* +30 /-30 or +28 / -30.5 or +32 / -32 PSF		FT WS* +37 /-41 PSF	● F T W +42 /-48 PSF	
	16' Wide Door	S +12.5/–14 PSF	S +15.5 / –17 PSF	F S* +20 /-21 PSF	SFT WS* +24 /-24.5 PSF	FTWS* +30 /-30 or +28 / -30.5 or +32 / -32 PSF		FT WS* +37 /-41 PSF	● F T W +42 /-48 PSF	
	18' Wide Door	S +12.5/–14 PSF	SELECT W3	F S* +20 /-21 PSF	SFT WS* +25 /-25 PSF	SELECT W6		S* +37/-37 PSF		
	8', 9' Wide Door	S +13/–15 PSF	SELECT W4	SELECT W4	● F S +25 /-32 PSF	76 F S +30 /-32 PSF	76SP F S* +32 /–37 PSF	F S* +38 /-42 PSF		
Models 76/76SP	10', 12' Wide Door	S +12.5/–14 PSF	SELECT W5	SELECT W5	SELECT W5	76 FT S* +30 /-30 PSF	76SP F S* +32 /-37 PSF	F S* +37 /–41 PSF		
	16' Wide Door	S +12.5/-14 PSF	SELECT W5	SELECT W5	SELECT W5	76 F S* +30 /-30 PSF	76SP F S* +32 /-37 PSF	F S* +37 /-41 PSF		
	18' Wide Door	S +12.5/-14 PSF								
	Standard Windows Impact Rated	Available		W Impact W F Florida A	/indows Avail pproved	able		e County App s Departmen	proved t of Insurance	e Approved

For W6–W8 doors over 9' wide, add 2" to the door opening.

*Long window availability is limited due to reinforcement requirements.

** For W1, Model T50 is used. Model T50 is a tongue-and-groove 1-layer door.